

FLECK® 2750

1-INCH CONTROL VALVE

IDEAL FOR RESIDENTIAL OR COMMERCIAL FILTER AND SOFTENER APPLICATIONS

FEATURES/BENEFITS

Lead-free brass valve body for superior strength and durability	Time-tested, hydraulically-balanced piston for service and regeneration
Continuous service flow rate of 26 GPM with a backwash of 25 GPM	Rugged-built electromechanical timer designed with heavy duty 3/8" wide plastic gears
Backwash capability accommodates softener tanks up to 30" and filter up to 21" in diameter	
Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system	

OPTIONS

Filter or softener control valves	NXT- Network(e)10(vuses on-T)40(-)TJ ET EM
No hard water bypass piston	
Brine cam auxiliary switch	
Electromechanical timer auxiliary switch	
Hot water	
Electromechanical 7- or 12-day time clock, meter delayed, or meter immediate regeneration	
Manual lever operations	

VALVE SPECIFICATIONS

Valve Material	Lead-free brass*
Inlet/Outlet	1" NPTM/BSPM
Cycles	3 or 5

FLOW RATES (50 PSI INLET) – VALVE ALONE

Continuous 15 psi drop	26 GPM
---------------------------	--------



FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 | WWW.PENTAIRAQUA.COM | CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com | pentair.com

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

40737 REV E JL14 © 2013 Pentair Residential Filtration, LLC. All Rights Reserved.