

Commercial Control Valves 273 and 278 Configurations

Penetration of the market for commercial control valves is growing rapidly. These valves are designed to meet a wide range of water and heating applications.



273 and 278 Configurations

- Simple, economic electronic time clock (chronometric)
- 7- or 99-day regenerative setting
- 12-volt operation
- Filter change indicator setting in one control
- Fully programmable cycle times
- Setting in 1-pound increments
- Operates 255, 263, 268, 273, 278 and Magnum® IT with one controller

762 Demand

- Simple, economic electronic demand (volumetric)
- 12-volt operation
- 28-day variable reserve
- Automatic capacity
- Fully programmable cycle times
- Setting in 1-pound increments
- Operates 255, 263, 268, 273, 278, and Magnum IT with one controller

764 Demand

- Simple, economic electronic demand (volumetric)
- Multi-tank applications (twin alternating tank parallel)
- Operates 255, 263, 268, 273, 278, and Magnum IT with one controller





99

Age Group	Total (%)	Male (%)	Female (%)	Unknown (%)
18-24	100	100	100	100
25-34	100	100	100	100
35-44	100	100	100	100
45-54	100	100	100	100
55-64	100	100	100	100
65+	100	100	100	100

Injector* Performance

Logix™ Series Controllers

Injector "H" (Light Purple)
For 9-inch Tanks

Injector "J" (Light Blue)

